



Hon. Pedro R. Pierluisi Urrutia
Gobernador

Lcda. Karla G. Mercado Rivera
Administradora y Principal Oficial de Compras

ENMIENDA NÚM. 2

SUBASTA FORMAL 23J-03153 PARA REPARACIÓN Y REHABILITACIÓN DE FACILIDADES DEL DEPARTAMENTO DE JUSTICIA DEL GOBIERNO DE PUERTO RICO

ASUNTO: VARIOS

Se notifica a los licitadores interesados en participar en la Subasta de referencia la siguiente enmienda:

- I. Se enmienda el inciso 4 **Término de Entrega** del pliego de la Subasta 23J-03153, para que lea como sigue:

*“4’. El contratista tendrá un **MÁXIMO de 12 meses** calendario, a partir de la fecha de la orden de comienzo de ejecución de los trabajos para culminar la obra.”*

- II. Se aneja **Tabla de Cotizar Enmendada I**, la cual tendrán que utilizar para presentar su oferta.

Todos los demás términos y condiciones permanecen sin alterar.

Héctor Ortiz Méndez
Administrador Auxiliar
Área de Adquisiciones

Joel Fontáñez González
Oficial de Licitación Interino

Emitido hoy lunes, 13 de febrero de 2023
En San Juan, Puerto Rico



Partida	Descripción	Unidad	Cantidad	Precio Unitario	Precio Total	Marca y Modelo	Tiempo de Entrega	Garantía	Ley % de Preferencia (si aplica)
B1 - ARCHITECTURE									
1	WINDOWS SEALANT								
	REMOVE AND REPLACE 20 EACH (DIMENSION VERIFIED ON FIELD AND AMOUNT FOUND = 12) OF LOUVERED WINDOWS WATERPROOF SEAL, 2.5 FT LONG X 2 FT HIGH REMOVE AND PROPERLY DISPOSE EXISTING LOUVERED WINDOW WATERPROOF SEAL.APPLY WINDOW WATERPROOF SEAL THROUGHOUT THE LOUVERED WINDOWS EXTERIOR PERIMETER 1.83 FT (H) X 6.92 FT (W) .	Each	12						
2	JALOUSIE WINDOWS ALUMINIUM								
	REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. FOR THOSE WINDOWS LOWER TO THE GROUND, REDUCE WINDOW SIZE AND CONTINUE THE CONCRETE WALL UNDER THE WINDOW SILL TO MAKE POSSIBLE THE ELEVATION OF THE WINDOW. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETERREDUCE EXISTING WINDOW OPENING AS PER ITEM #3. FINISHED WALL THICKNESS SHALL MATCH EXISTING. REFER TO B1-A-101 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	13						
3	CONCRETE WALL								
	REDUCE WINDOW OPENING SIZE AND CONTINUE THE CONCRETE WALL UNDER THE WINDOW SILL TO MAKE POSSIBLE THE ELEVATION OF THE WINDOW. FOR WINDOWS IN ITEM #2. FINISHED WALL THICKNESS SHALL MATCH EXISTING. REFER TO WINDOW SCHEDULE AND STRUCTURAL DWGS.	SF	270						
4	JALOUSIE WINDOWS ALUMINIUM								
	REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B1-A-101 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	6						
5	JALOUSIE WINDOWS ALUMINIUM								
	REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B1-A-101 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	2						
6	JALOUSIE WINDOWS ALUMINIUM								
	REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. FOR THOSE WINDOWS LOWER TO THE GROUND, REDUCE WINDOW SIZE AND CONTINUE THE CONCRETE WALL UNDER THE WINDOW SILL TO MAKE POSSIBLE THE ELEVATION OF THE WINDOW. AS MENTIONED IN ITEM #7. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REDUCE WINDOW OPENING AS PER ITEM #7. REFER TO B1-A-101 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	4						
7	CONCRETE WALL								
	REDUCE WINDOW OPENING SIZE AND CONTINUE THE CONCRETE WALL UNDER THE WINDOW SILL TO MAKE POSSIBLE THE ELEVATION OF THE WINDOW. FOR WINDOWS IN ITEM 6. FINISHED WALL THICKNESS SHALL MATCH EXISTING. REFER TO WINDOW SCHEDULE AND STRUCTURAL DWGS.	SF	35						
8	JALOUSIE WINDOWS ALUMINIUM								
	REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B1-A-101 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	1						
9	FIXED GLASS WINDOW								
	REMOVE AND REPLACE 4 EACH OF FIXED GLASS WINDOW, 2.92 FEET (W) X 3.67 FEET (H). REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. WHEN REPLACING THE TWO (2) FIXED GLASS WINDOWS WITH 1/4 INCH THICK TEMPERED GLASS, REPLACE WITH 1/2 INCH THICK TEMPERED GLASS. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B1-A-101 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	4						

[illegible]

B1 - ELECTRICAL

[illegible]

Partida	Descripción	Unidad	Cantidad	Precio Unitario	Precio Total	Marca y Modelo	Tiempo de Entrega	Garantía	Ley % de Preferencia (si aplica)
B2 - ARCHITECTURE									
1	JALOUSIE WINDOWS ALUMINUM REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS.REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B2-A-101 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	14						
2	JALOUSIE WINDOWS ALUMINUM REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS.REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B2-A-101 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	2						
3	FIXED LOUVEREDWINDOWS REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS.REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B2-A-101 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	2						
4	EXTERIOR PAINT PREPARE AND REPAINT 2,880 SF OF EXTERIOR PAINT (240 FT (L) x 12 FT (H).PRESSURE WASH SURFACES AND SCRABE BUILDING PERIMETER WALLS AS NECESSARY. PRIME AND APPLY TWO COATS OF PAINT. COLOR TO BE SELECTED BY ARCHITECT. REFER TO DRAWING SHEET AS-103 & SPECIFICATIONS FOR DETAILS.	SF	2880						
5	DOORS REPLACE ALL DOORS WITH STEEL WIND RESISTANT DOOR UNITS. WITH VISION PANEL. REMOVE AND DISPOSE EXISTING DOOR, HARDWARE AND RELATED ELEMENTS. INSTALL DOOR AS PER DOOR SCHEDULE & DETAILS FOR LOCATION AND DETAILS	Each	2						
6	WATERPROOFING MEMBRANE UPGRADE ROOF SYSTEM FOR BETTER PERFORMANCE AGAINST WIND AND WIND DRIVEN RAIN BY INSTALLING A TWO-PLY WATERPROOFING SYSTEM COMPRISED OF ONE SBS MODIFIED BITUMINOUS MEMBRANE, LIGHTWEIGHT BASE SHEET, 35 TO 47 MILS AND ONE SBS MODIFIED BITUMINOUS MEMBRANE, GRAVULE SURFACE CAP SHEET. POLYESTER REINFORCED. 150 TO 160 MILS. PROTECTED WITH ALUMINUM METAL FLASHING (60 FT (L) x 60 FT (W). REMOVE AND DISPOSE EXISTING ROOF WATERPROOFING SYSTEM COMPLYING WITH APPLICABLE LAWS AND REGULATIONS. INSTALL SBS MODIFIED BITUMINOUS MEMBRANE, REFER TO TECH. SPECS. FOR DETAILS. THIS AREA INCLUDES BUILDING 2 AND PART OF THE COVERED CORRIDORS. SEE GENERAL ROOF PLAN FOR DETAILS.	SF	3600						
7	WATERPROOFING TERMINATION-FLASHING REMOVE AND REPLACE 480 LF OF METAL CAP FLASHING (480 LF (L) x 2 IN (W). REMOVE AND DISPOSE EXISTING ROOF WATERPROOFING SYSTEM COMPLYING WITH APPLICABLE LAWS AND REGULATIONS. INSTALL CAP FLASHING AND RELATED WATERPROOFING SYSTEM AS PER ROOF DETAILS. REFER TO DRAWINGS FOR ROOF DETAILS.	LF	480						
8	INTERIOR PAINT PREPARE AND REPAINT 2,880 SF OF INTERIOR PAINT (240 FT (L) x 12 FT (H). PREPARE SURFACE AND SCRABE BUILDING INTERIOR PERIMETER WALLS AS NECESSARY. PRIME AND APPLY TWO COATS OF PAINT. COLOR TO BE SELECTED BY ARCHITECT. ONLY PAINT INTERIOR PERIMETER WALLS. REFER TO DRAWING SHEET AS-104 & SPECIFICATIONS FOR DETAILS.	SF	2,880						
1	MINI SPLIT AC Remove and replace 2 each of G4C/CG43EK012PH3H11C/ Mini Split AC units (12,000 BTU) wall mounted, 3 ft long x 0.5 ft wide x 1.5 ft high. Provide anchoring system for roof top A/C units. Remove / Demolish and Replace Mini Split AC unit(s) as indicated in drawings. B2-DM2-01, B2-M2-01, M1-01, M3-01	Each	2						
B2-GEN	GENERAL CONDITIONS	Each	1						

Note: Refiérase a los ANEIOS 6, 7, 8, 12,13 según presentado por la Entidad Patrocinaria. Las garantías mínimas en esta subasta Formal serán las establecidas en el Anexo 6: Technical Specifications Facilidades Departamento de Justicia PW-6661.

Precio Total: _____

Nombre del Licitador: _____ Firma del Licitador: _____

Partida	Descripción	Unidad	Cantidad	Precio Unitario	Precio Total	Marca y Modelo	Tiempo de Entrega	Garantía	Ley % de Preferencia (si aplica)
B3 - ARCHITECTURE									
1	JALOUSIE WINDOWS ALUMINUM								
	REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B3-A-101, B3-A-102 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	24						
2	JALOUSIE WINDOWS ALUMINUM								
	REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B3-A-101, B3-A-102 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	24						
3	JALOUSIE WINDOWS ALUMINUM								
	REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B3-A-101, B3-A-102 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	24						
4	EXTERIOR PAINT								
	PREPARE AND REPAINT 2,880 SF OF EXTERIOR PAINT (240 FT (1) x 12 FT (H)). PRESSURE WASH SURFACES AND SCRAPE BUILDING PERIMETER WALLS AS NECESSARY. PRIME AND APPLY TWO COATS OF PAINT. COLOR TO BE SELECTED BY ARCHITECT. REFER TO DRAWING SHEET AS-103 & SPECIFICATIONS FOR DETAILS.	SF	2,880						
5	DOORS								
	REPLACE ALL DOORS WITH STEEL WIND RESISTANT DOOR UNITS. REMOVE AND SAFELY STORE EXISTING SECURITY GATE LOCATED OVER EXISTING DOOR. REMOVE AND DISPOSE EXISTING DOOR. HARDWARE AND RELATED ELEMENTS. INSTALL DOOR AS PER DOOR SCHEDULE. REINSTALL SECURITY GATE SALVAGED DURING DEMOLITION OVER DOOR. REFER TO B3-A-101, B3-A-102 & DOOR SCHEDULE & DETAILS FOR LOCATION AND DETAILS	Each	24						
6	DOORS								
	REPLACE ALL DOORS WITH STEEL WIND RESISTANT DOOR UNITS. REMOVE AND DISPOSE EXISTING DOOR, HARDWARE AND RELATED ELEMENTS. INSTALL DOOR AS PER DOOR SCHEDULE. REFER TO B3-A-101, B3-A-102 & DOOR SCHEDULE & DETAILS FOR LOCATION AND DETAILS	Each	2						
7	WATERPROOFING MEMBRANE								
	UPGRADE ROOF SYSTEM FOR BETTER PERFORMANCE AGAINST WIND AND WIND DRIVEN RAIN BY INSTALLING A TWO-PLY WATERPROOFING SYSTEM COMPRISED OF ONE SBS MODIFIED BITUMINOUS MEMBRANE, LIGHTWEIGHT BASE SHEET, 35 TO 47 MILS AND ONE SBS MODIFIED BITUMINOUS MEMBRANE, GRANULE SURFACE CAP SHEET, POLYESTER REINFORCED, 150 TO 160 MILS. PROTECTED WITH ALUMINUM METAL FLASHING (95 FT (1) x 85 FT (W)). REMOVE AND DISPOSE EXISTING ROOF WATERPROOFING SYSTEM COMPLYING WITH APPLICABLE LAWS AND REGULATIONS. INSTALL SBS MODIFIED BITUMINOUS MEMBRANE. REFER TO TECH SPECS AND ROOF PLANS/DETAILS. THIS AREA INCLUDES BUILDING 3 AND PART OF THE COVERED CORRIDORS. SEE GENERAL ROOF PLAN FOR DETAILS.	SF	8,075						
8	WATERPROOFING TERMINATION-FLASHING								
	REMOVE AND REPLACE 352 LF OF METAL CAP FLASHING (352 LF (1) x 2 IN (W)). REMOVE AND DISPOSE EXISTING ROOF WATERPROOFING SYSTEM COMPLYING WITH APPLICABLE LAWS AND REGULATIONS. INSTALL CAP FLASHING AND RELATED WATERPROOFING SYSTEM AS PER ROOF DETAILS. REFER TO TECH SPECS FOR DETAILS.	LF	352						
9	INTERIOR PAINT								
	PREPARE AND REPAINT 2,880 SF OF INTERIOR PAINT (240 FT (1) x 12 FT (H)). PREPARE SURFACE AND SCRAPE BUILDING INTERIOR PERIMETER WALLS AS NECESSARY. PRIME AND APPLY TWO COATS OF PAINT. COLOR TO BE SELECTED BY ARCHITECT. ONLY PAINT INTERIOR PERIMETER WALLS ON THE FIRST AND SECOND LEVEL OF THE IDENTIFIED AREA. REFER TO DRAWING SHEET AS-104 & SPECIFICATIONS FOR DETAILS.	SF	2,880						
1	MINI SPLIT AC								
	Remove and replace 2 each of CLAC/CG43EX012PH3H1C/ Mini Split AC units (12,000 BTU) wall mounted, 3 ft long x 0.5 ft wide x 1.5 ft high Provide anchoring system for roof top A/C units. Remove / Demolish and Replace Mini Split unit(s) as indicated in drawings. B3-DW2-01B3-M2-01, M1-01, M3-01	Each	2						
B3-GEN	GENERAL CONDITIONS								
	Mobilization or demobilization, deliver/ charge for small equipment, placed in rear of, or towed by pickup truck	Each	1						

Note: Refirase a los ANEXOS 6, 7, 8, 14, 15 según presentado por la Entidad Recontrataria. Las garantías mínimas en esta Subasta Formal perten las establecidas en el Anexo 6. Technical Specifications Facilidades Departamento de Justicia PW-6661.

Precio Total: _____

Nombre del Licitador: _____ Firma del Licitador: _____

Precio Total:

Partida	Descripción	Unidad	Cantidad	Precio Unitario	Precio Total	Marca y Modelo	Tiempo de Entrega	Garantía	Ley % de Preferencia (si aplica)
B5 - ARCHITECTURE									
1	FIXED LOUVERED ALUMINUM								
2	REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B5-A-101, B5-A-102 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	7						
	JALOUSIE WINDOWS ALUMINUM								
3	REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B5-A-101, B5-A-102 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	19						
	JALOUSIE WINDOWS ALUMINUM								
4	REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B5-A-101, B5-A-102 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	6						
	FIXED LOUVERED ALUMINUM								
5	REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B5-A-101, B5-A-102 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	3						
	JALOUSIE WINDOWS ALUMINUM								
6	REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B5-A-101, B5-A-102 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	1						
	JALOUSIE WINDOWS ALUMINUM								
7	REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B5-A-101, B5-A-102 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	1						
	JALOUSIE WINDOWS ALUMINUM								
8	REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B5-A-101, B5-A-102 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	3						
	EXTERIOR PAINT								
9	PREPARE AND REPAINT 3,600 SF OF EXTERIOR PAINT (300 FT (L) x 12 FT (H). PRESSURE WASH SURFACES AND SCRAPE BUILDING PERIMETER WALLS AS NECESSARY. PRIME AND APPLY TWO COATS OF PAINT. COLOR TO BE SELECTED BY ARCHITECT. REFER TO DRAWING SHEET AS-103 & SPECIFICATIONS FOR DETAILS.	SF	3,600						
	INTERIOR PAINT								
10	PREPARE AND REPAINT 3,600 SF OF INTERIOR PAINT (300 FT (L) x 12 FT (H). PREPARE SURFACE AND SCRAPE BUILDING INTERIOR PERIMETER WALLS AS NECESSARY. PRIME AND APPLY TWO COATS OF PAINT. COLOR TO BE SELECTED BY ARCHITECT. REFER TO DRAWING SHEET AS-104 & SPECIFICATIONS FOR DETAILS.	SF	3,600						
	DOORS								
11	REPLACE ALL DOORS WITH STEEL, WIND RESISTANT DOOR UNITS, WITH VISION PANEL. REMOVE AND DISPOSE EXISTING DOOR, HARDWARE AND RELATED ELEMENTS. INSTALL DOOR AS PER DOOR SCHEDULE. REFER TO B5-A-101, B5-A-102 & DOOR SCHEDULE & DETAILS FOR LOCATION AND DETAILS	Each	7						
	DOORS								
	REPLACE ALL DOORS WITH STEEL, WIND RESISTANT DOOR UNITS. REMOVE AND DISPOSE EXISTING DOOR, HARDWARE AND RELATED ELEMENTS. INSTALL DOOR AS PER DOOR SCHEDULE. REFER TO B5-A-101, B5-A-102 & DOOR SCHEDULE & DETAILS FOR LOCATION AND DETAILS	Each	3						

Precio Total:

Partida	Descripción	Unidad	Cantidad	Precio Unitario	Precio Total	Marca y Modelo	Tiempo de Entrega	Garantía	Ley % de Preferencia (si aplica)
B7 - ARCHITECTURE									
1	JALOUSIE WINDOWS ALUMINUM								
	REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B7-A-101 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	8						
2	JALOUSIE WINDOWS ALUMINUM								
	REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B7-A-101 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	4						
3	JALOUSIE WINDOWS ALUMINUM								
	REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B7-A-101 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	16						
4	EXTERIOR PAINT								
	REPAIR 24 EACH OF PAINT DAMAGE ON RAIL. PRESURE WASH AND SCAPE/WIRE BRUSH ALL SURFACES AS NECESSARY. PRIME AND APPLY TWO COATS OF PAINT. COLOR TO BE SELECTED BY ARCHITECT. REFER TO B7-A-101 & A-204	Each	12						
5	DOORS								
	REPLACE ALL DOORS WITH STEEL WIND RESISTANT DOOR UNITS. REMOVE AND SAFELY STORE EXISTING SECURITY GATE LOCATED OVER EXISTING DOOR. REMOVE AND DISPOSE EXISTING DOOR, HARDWARE AND RELATED ELEMENTS. INSTALL DOOR AS PER DOOR SCHEDULE. REINSTALL SECURITY GATE SALVAGED, DURING DEMOLITION, OVER DOOR. REFER TO B7-A-101 & DOOR SCHEDULE & DETAILS FOR LOCATION AND DETAILS	Each	4						
6	DOORS								
	REPLACE ALL DOORS WITH STEEL WIND RESISTANT DOOR UNITS. REMOVE AND DISPOSE EXISTING DOOR, HARDWARE AND RELATED ELEMENTS. INSTALL DOOR AS PER DOOR SCHEDULE. REFER TO B7-A-101 & DOOR SCHEDULE & DETAILS FOR LOCATION AND DETAILS	Each	2						
7	WATERPROOFING MEMBRANE								
	UPGRADE ROOF SYSTEM FOR BETTER PERFORMANCE AGAINST WIND AND WIND DRIVEN RAIN BY INSTALLING A TWO-PLY WATERPROOFING SYSTEM COMPRISED OF ONE SBS MODIFIED BITUMINOUS MEMBRANE, LIGHTWEIGHT BASE SHEET, 35 TO 47 MILS AND ONE SBS MODIFIED BITUMINOUS MEMBRANE, GRANULE SURFACE CAP SHEET, POLYESTER REINFORCED, 150 TO 160 MILS, PROTECTED WITH ALUMINUM METAL FLASHING (60 FT (L) x 32 FT (W)). REMOVE AND DISPOSE EXISTING ROOF WATERPROOFING SYSTEM COMPLYING WITH APPLICABLE LAWS AND REGULATIONS. INSTALL SBS MODIFIED BITUMINOUS MEMBRANE. REFER TO TECH SPECS AND ROOF PLANS/DETAILS.	SF	1,920						
7	WATERPROOFING TERMINATION-FLASHING								
	REMOVE AND REPLACE 418 LF OF METAL CAP FLASHING (418 LF (L) x 2 IN (W)). REMOVE AND DISPOSE EXISTING ROOF WATERPROOFING SYSTEM COMPLYING WITH APPLICABLE LAWS AND REGULATIONS. INSTALL CAP FLASHING AND RELATED WATERPROOFING SYSTEM AS PER ROOF DETAILS. REFER TO TECH SPECS FOR DETAILS.	LF	418						
8	INTERIOR PAINT								
	PREPARE AND REPAINT 2,760 SF OF INTERIOR PAINT (120 FT (L) x 23 FT (H)). PREPARE SURFACE AND SCAPE BUILDING INTERIOR PERIMETER WALLS AS NECESSARY. PRIME AND APPLY TWO COATS OF PAINT. COLOR TO BE SELECTED BY ARCHITECT. ONLY PAINT INTERIOR PERIMETER WALLS ON THE FIRST AND SECOND LEVEL OF THE IDENTIFIED AREA. REFER TO DRAWING SHEET AS-104 & SPECIFICATIONS FOR DETAILS.	SF	2,760						
B7 - ELECTRICAL									
1	LUMINAIRE								
	REMOVE AND REPLACE 1 EACH OF HIGH PRESSURE SODIUM LUMINAIRE, 3 FT LONG X 1 FT WIDE. LUMINAIRE DEMOLITION: REMOVE AND PROPERLY DISPOSE ALL EXISTING HIGH PRESSURE SODIUM LUMINAIRE. REPLACE LUMINAIRE WITH EQUIVALENT UNITS. FOR ADDITIONAL INFORMATION AND BASIS OF DESIGN PRODUCT AND MANUFACTURER, REFER TO DRAWINGS B7-WSE-01.	Each	1						

Note: Refiérase a los ANEJOS 6, 7, 8, 22 según presentado por la Entidad Peticionaria. Las garantías mínimas en esta subasta Formal serán las establecidas en el Anexo 6: Technical Specifications Facilidades Departamento de Justicia PW-6661.

Partida	Descripción	Unidad	Cantidad	Precio Unitario	Precio Total	Tiempo de Entrega	Garantía	Ley % de Preferencia (si aplica)
B9 - ARCHITECTURE								
1	JALOUSIE WINDOWS ALUMINUM REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B9-A-101 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	6					
2	JALOUSIE WINDOWS ALUMINUM REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B9-A-101 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	6					
3	JALOUSIE WINDOWS ALUMINUM REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B9-A-101 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	6					
4	DOORS REPLACE ALL DOORS WITH STEEL, WIND RESISTANT DOOR UNITS. REMOVE AND SAFELY STORE EXISTING SECURITY GATE LOCATED OVER EXISTING DOOR. REMOVE AND DISPOSE EXISTING DOOR, HARDWARE AND RELATED ELEMENTS. INSTALL DOOR AS PER DOOR SCHEDULE. REINSTALL SECURITY GATE SALVAGED, DURING DEMOLITION, OVER DOOR. REFER TO B9-A-101 & DOOR SCHEDULE & DETAILS FOR LOCATION AND DETAILS	Each	6					
5	WATERPROOFING MEMBRANE UPGRADE ROOF SYSTEM FOR BETTER PERFORMANCE AGAINST WIND AND WIND DRIVEN RAIN BY INSTALLING A TWO-PLY WATERPROOFING SYSTEM COMPRISED OF ONE SBS MODIFIED BITUMINOUS MEMBRANE, LIGHTWEIGHT BASE SHEET, .35 TO .47 MILS AND ONE SBS MODIFIED BITUMINOUS MEMBRANE. GRANULE SURFACE CAP SHEET. POLYESTER REINFORCED, .150 TO .160 MILS. PROTECTED WITH ALUMINUM METAL FLASHING (65 FT (L) x 26 FT (W)). REMOVE AND DISPOSE EXISTING ROOF WATERPROOFING SYSTEM COMPLYING WITH APPLICABLE LAWS AND REGULATIONS. INSTALL SBS MODIFIED BITUMINOUS MEMBRANE. REFER TO TECH SPECS AND ROOF PLANS/DETAILS.	SF	1,690					
6	WATERPROOFING TERMINATION FLASHING REMOVE AND REPLACE 190 LF OF METAL CAP FLASHING (190 LF (L) x 2 IN (W)). REMOVE AND DISPOSE EXISTING ROOF WATERPROOFING SYSTEM COMPLYING WITH APPLICABLE LAWS AND REGULATIONS. INSTALL CAP FLASHING AND RELATED WATERPROOFING SYSTEM AS PER ROOF DETAILS. REFER TO TECH SPECS FOR DETAILS.	LF	190					
B9-GEN	GENERAL CONDITIONS	Each	1					
Note: Referéase a los ANEJOS 6, 7, 8, 23 según presentado por la Entidad Peticionaria. Las garantías mínimas en esta Subasta Formal serán las establecidas en el Anexo 6: Technical Specifications Facilidades Departamento de Justicia PW-6661.								
Mobilization or demobilization, delivery charge for small equipment, placed in rear of, or towed by pickup truck				Each	1			
Precio Total:								
Nombre del Licitador: _____ Firma del Licitador: _____								

Partida	Descripción	Unidad	Cantidad	Precio Unitario	Precio Total	Tiempo de Entrega	Garantía	Ley % de Preferencia (si aplica)
B10 - ARCHITECTURE								
1	JALOUSIE WINDOWS ALUMINUM							
	REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B10-A-101 & A-608 FOR WINDOW LOCATION & SCHEDULE	Each	6					
2	JALOUSIE WINDOWS ALUMINUM							
	REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B10-A-101 & A-608 FOR WINDOW LOCATION & SCHEDULE	Each	6					
3	JALOUSIE WINDOWS ALUMINUM							
	REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B10-A-101 & A-608 FOR WINDOW LOCATION & SCHEDULE	Each	6					
4	DOORS							
	EXISTING DOOR. REMOVE AND DISPOSE EXISTING DOOR, HARDWARE AND RELATED ELEMENTS. INSTALL DOOR AS PER DOOR SCHEDULE. REINSTALL SECURITY GATE SALVAGED, DURING DEMOLITION, OVER DOOR. REFER TO B10-A-101 & A-603 FOR DOOR LOCATION & SCHEDULE	Each	6					
5	WATERPROOFING MEMBRANE							
	UPGRADE ROOF SYSTEM FOR BETTER PERFORMANCE AGAINST WIND AND WIND DRIVEN RAIN BY INSTALLING A TWO-PLY WATERPROOFING SYSTEM COMPRISED OF ONE SBS MODIFIED BITUMINOUS MEMBRANE, LIGHTWEIGHT BASE SHEET, 35 TO 47 MILS AND ONE SBS MODIFIED BITUMINOUS MEMBRANE, GRANULE SURFACE CAP SHEET, POLYESTER REINFORCED, 150 TO 160 MILS, PROTECTED WITH ALUMINUM METAL FLASHING (65 FT (1) x 26 FT (W)). REMOVE AND DISPOSE EXISTING ROOF WATERPROOFING SYSTEM COMPLYING WITH APPLICABLE LAWS AND REGULATIONS. INSTALL SBS MODIFIED BITUMINOUS MEMBRANE. REFER TO TECH SPECS AND ROOF PLANS/DETAILS.	SF	1,690					
6	WATERPROOFING TERMINATION-FLASHING							
	REMOVE AND REPLACE 190 LF OF METAL CAP FLASHING (190 LF (1) x 2 IN (W)). REMOVE AND DISPOSE EXISTING ROOF WATERPROOFING SYSTEM COMPLYING WITH APPLICABLE LAWS AND REGULATIONS. INSTALL CAP FLASHING AND RELATED WATERPROOFING SYSTEM AS PER ROOF DETAILS. REFER TO TECH SPECS FOR DETAILS.	LF	190					
B10-GEN	GENERAL CONDITIONS							
	Mobilization or demobilization, delivery charge for small equipment, placed in rear of, or towed by pickup truck	Each	1					

Note: Referirse a los ANEIOS 6, 7, 8, 24 según presentado por la Entidad Peticionaria. Las garantías mínimas en esta Subasta Formal serán las establecidas en el Anejo 6: Technical Specifications Facilidades Departamento de Justicia PW-6661.

Precio Total: _____

Nombre del Licitador: _____

Firma del Licitador: _____

Partida	Descripción	Unidad	Cantidad	Precio Unitario	Precio Total	Marca y Modelo	Tiempo de Entrega	Garantía	Ley % de Preferencia (si aplica)
B11 - ARCHITECTURE									
1	JALOUSIE WINDOWS ALUMINUM								
	REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B11-A-101 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	19						
2	JALOUSIE WINDOWS ALUMINUM								
	REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B11-A-101 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	2						
3	JALOUSIE WINDOWS ALUMINUM								
	REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. FOR THOSE WINDOWS LOWER TO THE GROUND. REDUCE WINDOW SIZE AND CONTINUE THE CONCRETE WALL UNDER THE WINDOW SILL TO MAKE POSSIBLE THE ELEVATION OF THE WINDOW. AS MENTIONED IN ITEM #4. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REDUCE EXISTING WINDOW OPENING AS PER ITEM #4. FINISHED WALL THICKNESS SHALL MATCH EXISTING. REFER TO B11-A-101 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	2						
4	CONCRETE WALL								
	REDUCE WINDOW OPENING SIZE AND CONTINUE THE CONCRETE WALL UNDER THE WINDOW SILL TO MAKE POSSIBLE THE ELEVATION OF THE WINDOW. FOR WINDOWS IN ITEM #3. REDUCE EXISTING WINDOW OPENING AS PER ITEM #3. FINISHED WALL THICKNESS SHALL MATCH EXISTING. REFER TO WINDOW SCHEDULE AND STRUCTURAL DWGS.	Each	2						
5	FIXED LOUVERED WINDOWS								
	REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B11-A-101 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	2						
6	FIXED LOUVERED WINDOWS								
	REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B11-A-101 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	1						
7	FIXED LOUVERED WINDOWS								
	REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B11-A-101 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	1						
8	FIXED LOUVERED WINDOWS								
	REPLACE ALL WINDOWS WITH IMPACT AND WIND-RESISTANT UNITS. REMOVE AND PROPERLY DISPOSE EXISTING WINDOW AND RELATED ELEMENTS. INSTALL WINDOW AS PER WINDOW SCHEDULE. APPLY WATERPROOFING SEALANT THROUGHOUT WINDOW EXTERIOR PERIMETER. REFER TO B11-A-101 & WINDOW SCHEDULE & ELEVATIONS FOR LOCATION AND DETAILS	Each	1						
9	EXTERIOR PAINT								
	PREPARE AND REPAINT 3,444 SF OF EXTERIOR PAINT (287 FT (L) x 12 FT (H). PRESSURE WASH SURFACES AND SCRAPE BUILDING PERIMETER WALLS AS NECESSARY. PRIME AND APPLY TWO COATS OF PAINT. COLOR TO BE SELECTED BY ARCHITECT. REFER TO DRAWING SHEET AS-103 & SPECIFICATIONS FOR DETAILS.	SF	3,444						
10	DOORS								
	REPLACE ALL DOORS WITH STEEL WIND RESISTANT DOOR UNITS. TRANSOM AND SIDE LIGHTS. REMOVE AND DISPOSE EXISTING DOOR, HARDWARE AND RELATED ELEMENTS. INSTALL DOOR AS PER DOOR SCHEDULE. REFER TO B11-A-101 & DOOR SCHEDULE & DETAILS FOR LOCATION AND DETAILS	Each	2						

[illegible]

Partida	Descripción	Unidad	Cantidad	Precio Unitario	Precio Total	Marca y Modelo	Tiempo de Entrega	Garantía	Ley % de Preferencia (si aplica)
ALTERNAS									
1	ALTERNIA 1 ADITIVA EXTERIOR PAINTING (BUILDINGS #1,3,4,7, 9, 10 Y 11). ALTERNATE PRICE QUOTATIONS SHALL INCLUDE ALL LABOR, MATERIALS, EQUIPMENT, OVERHEAD, INSURANCE, BONDS, APPLICABLE TAXES, PROFIT, ETC., NECESSARY TO ADD OR TO DEDUCT THE TOTAL AMOUNT OF EACH ALTERNATE PROPOSAL. ALL CONTRACT DOCUMENTS CONDITIONS AND REQUIREMENTS APPLY TO THE ALTERNATE WORK.	SF	51,384						
2	ALTERNIA 2 ADITIVA FLUID APPLIED ROOFING (GABLE: BLDG. #1, #2 & #5) (MONO PITCH: BLDG. #3 & #4) (DOUBLE PITCH: BLDG. #7 & #8). ALTERNATE PRICE QUOTATIONS SHALL INCLUDE ALL LABOR, MATERIALS, EQUIPMENT, OVERHEAD, INSURANCE, BONDS, APPLICABLE TAXES, PROFIT, ETC., NECESSARY TO ADD OR TO DEDUCT THE TOTAL AMOUNT OF EACH ALTERNATE PROPOSAL. ALL CONTRACT DOCUMENTS CONDITIONS AND REQUIREMENTS APPLY TO THE ALTERNATE WORK.	LS	1						
3	ALTERNIA 3 ADITIVA EXTERIOR PAINT -WINDOW SECURITY BARS (BLDG. # 3, #4, #7, #8, #9 & #10). ALTERNATE PRICE QUOTATIONS SHALL INCLUDE ALL LABOR, MATERIALS, EQUIPMENT, OVERHEAD, INSURANCE, BONDS, APPLICABLE TAXES, PROFIT, ETC., NECESSARY TO ADD OR TO DEDUCT THE TOTAL AMOUNT OF EACH ALTERNATE PROPOSAL. ALL CONTRACT DOCUMENTS CONDITIONS AND REQUIREMENTS APPLY TO THE ALTERNATE WORK.	SF	4,236						
4	ALTERNIA 4 ADITIVA SECURITY GATE/FENCE REPLACEMENT (BLDG. #1). ALTERNATE PRICE QUOTATIONS SHALL INCLUDE ALL LABOR, MATERIALS, EQUIPMENT, OVERHEAD, INSURANCE, BONDS, APPLICABLE TAXES, PROFIT, ETC., NECESSARY TO ADD OR TO DEDUCT THE TOTAL AMOUNT OF EACH ALTERNATE PROPOSAL. ALL CONTRACT DOCUMENTS CONDITIONS AND REQUIREMENTS APPLY TO THE ALTERNATE WORK.	LS	1						
5	ALTERNIA 5 ADITIVA EXTERIOR PAINT SECURITY GATE (BLDG. #1). ALTERNATE PRICE QUOTATIONS SHALL INCLUDE ALL LABOR, MATERIALS, EQUIPMENT, OVERHEAD, INSURANCE, BONDS, APPLICABLE TAXES, PROFIT, ETC., NECESSARY TO ADD OR TO DEDUCT THE TOTAL AMOUNT OF EACH ALTERNATE PROPOSAL. ALL CONTRACT DOCUMENTS CONDITIONS AND REQUIREMENTS APPLY TO THE ALTERNATE WORK.	LS	1						
6	ALTERNIA 6 ADITIVA INSTALL SECURITY CAMERAS (BLDG. #1, #7 & #11). ALTERNATE PRICE QUOTATIONS SHALL INCLUDE ALL LABOR, MATERIALS, EQUIPMENT, OVERHEAD, INSURANCE, BONDS, APPLICABLE TAXES, PROFIT, ETC., NECESSARY TO ADD OR TO DEDUCT THE TOTAL AMOUNT OF EACH ALTERNATE PROPOSAL. ALL CONTRACT DOCUMENTS CONDITIONS AND REQUIREMENTS APPLY TO THE ALTERNATE WORK.	LS	1						
7	ALTERNIA 7 ADITIVA CEMENT PLASTER: REMOVE AND PROPERLY DISPOSE SPALLED, CRACKED OR DAMAGED CEMENT PLASTER FROM WALLS OR CEILINGS (INTERIOR OR EXTERIOR). PREPARE SURFACE AND PROVIDE NEW CEMENT PLASTER, WHERE INDICATED (BLDG. #1, #2, #3, #4, #5, #7, #8, #9, #10, #11). ALTERNATE PRICE QUOTATIONS SHALL INCLUDE ALL LABOR, MATERIALS, EQUIPMENT, OVERHEAD, INSURANCE, BONDS, APPLICABLE TAXES, PROFIT, ETC., NECESSARY TO ADD OR TO DEDUCT THE TOTAL AMOUNT OF EACH ALTERNATE PROPOSAL. ALL CONTRACT DOCUMENTS CONDITIONS AND REQUIREMENTS APPLY TO THE ALTERNATE WORK.	SF	2,500						

Note: Reférase a los ANEJOS 6, 7, 8 según presentado por la Entidad Peticionaria. En el proceso de evaluación de las propuestas y el cliente, deciden si aceptan (o no aceptan) una, algunas todas o ninguna de las Alternas. Las garantías mínimas en esta Subasta Formal serán las establecidas en el Anejo 6: Technical Specifications, Facilidades Departamento de Justicia PW-5661.

Precio Total: _____

Nombre del Licitador: _____ Firma del Licitador: _____